



**1000 RACING SERIES**



# 1000 RACING SERIES



**Model MT2422W-1000**  
(featuring *optional* ABS Chrome Wheel Liners)

## SPECIFICATIONS

MODEL	MT2022W-1000	MT2024W-1000	MT2422W-1000	MT2424W-1000
BODY: LENGTH	20'0"	20'0"	24'0"	24'0"
WIDTH	98 1/4"	98 1/4"	98 1/4"	98 1/4"
OVERALL: LENGTH	24'0"	24'0"	28'0"	28'0"
WIDTH	102"	102"	102"	102"
HEIGHT	8'7"	8'7"	8'7"	8'7"
INTERIOR: LENGTH	19'9"	19'9"	23'9"	23'9"
WIDTH	7'11"	7'11"	7'11"	7'11"
HEIGHT	6'8"	6'8"	6'8"	6'8"
WHEEL BOX CLEARANCE	81"	81"	81"	81"
PLATFORM HEIGHT	17"	17"	17"	17"
TIRE SIZE/LOAD RANGE	15" /C	15" /D	15" /C	15" /D
WHEEL BOLT PATTERN	5-Bolt/4.5	6-Bolt/5.5	5-Bolt/4.5	6-Bolt/5.5
HITCH TO TOP OF BALL	19"	19"	19"	19"
HITCH WEIGHT (% of Curb Weight)	10-15%	10-15%	10-15%	10-15%
CURB WEIGHT (lb.)	3350	3675	3645	3970
GVWR (lb.)	7,000	10,000	7,000	10,000
GAWR (lb.)	7,000	10,000	7,000	10,000
AVG. PAYLOAD CAPACITY (lb.)	3650	6325	3355	6030
REAR RAMP DOOR: WIDTH	87 1/2"	87 1/2"	87 1/2"	87 1/2"
HEIGHT	79"	79"	79"	79"
WARRANTY	3-Years	3-Years	3-years	3-Years

Specifications and features subject to change without notice.

## FEATURES

- Rear Ramp Door with Dual Spring Assist Cables
- Plywood Ramp Toe Extension
- Rear Swing Down Stabilizer Jacks
- Reinforced 4" Recessed Beavertail
- 36" Side Door with Full-Length Cam Lock
- Recessed Step at Side Door
- 3/4" Exterior Grade Plywood Floor (*undercoated*)
- 1/4" Plywood Interior Sidewall Liner
- 12-Volt Dome Lights (2) with Wall Switch
- Sealed Beam Oval Tail Lights
- 18" ATP Stone Guard with Intergrated Corners



Standard Interior Floor and Sidewall Liner with *optional* D-Ring Tie-Downs

- Smooth Aluminum Fenderettes
- Prefinished Galvanealed Steel White Exterior Skin
- Non-Corrosive Mechanical Fasteners
- Galvanized Steel Roof
- Tubular Steel Main Rails
- Full Height C-Channel Crossmembers & Outriggers
- Chassis Fully Primed and Painted Silver
- 3-Piece A-Frame with 2 5/16" Ball Coupler Hitch
- Top Crank Jack Ram Hoist with Sand Pad
- D.O.T. Compliant Safety Chains with Clevis Slip Hook & Latch
- Torflex® Rubber Torsion Tandem Axles (*10° Up Trailing*)
- E-Z Lube Hubs
- 15" Bias Belted Tires on Silver Mod Wheels
- Electric Brakes with Weather Resistant Wiring
- Wet Cell Battery Breakaway System
- 7-way Pigtail Connector
- Flared Stripe Racing Graphics (*choice of red, black or blue*)

Authorized Wells Cargo Dealer:



©Wells Cargo, Inc. 2003  
Form: MT1000-203



# 2000 RACING SERIES





LED Wraparound Tail Lights

## Model MT2824W-2000

(Features optional equipment available at an additional charge)



Front Turbo Cap



Rear Turbo Cap

# 2000 RACING SERIES

(800) 348-7353 [www.wellscargo.com](http://www.wellscargo.com)

## FEATURES:

- Rear Ramp Door with Dual Spring Assist
- Rear Cornerpost Stabilizer Jacks
- Reinforced 4' Recessed Beavertail
- 36" Side Door with Rotary Style Flush Lock
- Recessed Interior Step at Side Door
- 3/4" Exterior Grade Plywood Floor (undercoated)
- 1/4" Plywood Interior Sidewall Liner
- 12-Volt Dome Lights (2) with Wall Switch
- LED Wraparound Stop/Tail/Turn Lights
- 24" ATP Stone Guard with Intergrated Corners
- Front & Rear Fiberglass Turbo Caps
- Satin Anodized Aluminum Fenderettes
- .030 Prefinished Aluminum Exterior Skin (11 colors)
- Non-Corrosive Mechanical Fasteners
- Aluminum Seamless Roof
- Tubular Steel Main Rails
- Full Height C-Channel Crossmembers & Outriggers
- Chassis Fully Undercoated with CPC (Corrosion Preventative Compound)
- 3-Piece A-Frame with 2<sup>9</sup>/<sub>16</sub>" Ball Coupler Hitch
- Top Crank Jack Ram Hoist with Sand Pad
- D.O.T. Compliant Safety Chains with Clevis Slip Hook & Latch
- Torflex® Rubber Torsion Tandem Axles (10° Up Trailing)
- E-Z Lube Hubs
- 15" Radial Tires on Silver Spoke Wheels
- Electric Brakes with Weather Resistant Wiring
- Wet Cell Battery Breakaway System
- 7-way Pigtail Connector



# SPECIFICATIONS

## MotorTrac®

	MODEL	Overall:				Interior:			Axle #	Rear Door Width	Rear Door Height	Platform Height	Hitch To Top Of Ball	Wheel Box Clearance	Curb Weight**	Hitch Weight	GVWR	GAWR	Average Payload Capacity
		L	W (Axle)	W (Body)	H	L	W	H											
2 Ton	MT 1822	22'0"	102"	8'2 1/4"	8'5"	17'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	2900	*	7,700	7,000	4,800
	MT 2022	24'0"	102"	8'2 1/4"	8'5"	19'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	3100	*	7,700	7,000	4,600
	MT 2222	26'0"	102"	8'2 1/4"	8'5"	21'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	3300	*	7,700	7,000	4,400
	MT 2422	28'0"	102"	8'2 1/4"	8'5"	23'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	3500	*	7,700	7,000	4,200
4 Ton	MT 1824	22'0"	102"	8'2 1/4"	8'5"	17'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	2900	*	10,000	10,000	7,100
	MT 2024	24'0"	102"	8'2 1/4"	8'5"	19'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	3100	*	10,000	10,000	6,900
	MT 2224	26'0"	102"	8'2 1/4"	8'5"	21'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	3300	*	10,000	10,000	6,700
	MT 2424	28'0"	102"	8'2 1/4"	8'5"	23'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	3500	*	10,000	10,000	6,500
	MT 2624	30'0"	102"	8'2 1/4"	8'5"	25'9"	7'11"	6'6"	2	90 3/4"	79"	17"	19"	81"	4000	*	10,000	10,000	6,000
	MT 2824	32'0"	102"	8'2 1/4"	8'7"	27'9"	7'11"	6'6"	2	90 3/4"	80"	18"	21"	81"	4500	*	10,000	10,000	5,500
	MT 3224	36'0"	102"	8'2 1/4"	8'7"	31'9"	7'11"	6'6"	2	90 3/4"	80"	18"	21"	81"	4850	*	10,000	10,000	5,150

\* 10-15% of Curb Weight depending on chosen options.  
 \*\* May vary depending upon chosen options.

## MotorTrac® Gooseneck

	MODEL	Overall:				Interior:				Axle #	Rear Door Width	Rear Door Height	Platform Height	Wheel Box Clearance	Curb Weight	GVWR	GAWR	Average Payload Capacity	
		L	W (Axle)	W (Body)	H	L (Lower Deck)	L (Upper Deck)	W	H (Lower Deck)										H*** (Upper Deck)
5 Ton	MTG 2425	24'0"	102"	8'2 1/4"	8'8"	15'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	4120	14,700	12,000	10,580
	MTG 2825	28'0"	102"	8'2 1/4"	8'8"	19'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	4610	14,700	12,000	10,090
	MTG 3225	32'0"	102"	8'2 1/4"	8'8"	23'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	5100	14,700	12,000	9,600
	MTG 3625	36'0"	102"	8'2 1/4"	8'8"	27'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	5580	14,700	12,000	9,120
	MTG 4025	40'0"	102"	8'2 1/4"	8'8"	31'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	6060	14,700	12,000	8,640
	MTG 4425	44'0"	102"	8'2 1/4"	8'8"	35'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	6540	14,700	12,000	8,160
9 Ton	MTG 4825	48'0"	102"	8'2 1/4"	8'8"	39'10"	7'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	7020	14,700	12,000	7,680
	MTG 2439	24'0"	102"	8'2 1/4"	8'8"	15'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	4506	22,500	18,000	17,994
	MTG 2839	28'0"	102"	8'2 1/4"	8'8"	19'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	4996	22,500	18,000	17,504
	MTG 3239	32'0"	102"	8'2 1/4"	8'8"	23'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	5486	22,500	18,000	17,014
	MTG 3639	36'0"	102"	8'2 1/4"	8'8"	27'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	5966	22,500	18,000	16,534
	MTG 4039	40'0"	102"	8'2 1/4"	8'8"	31'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	6446	22,500	18,000	16,054
9 Ton	MTG 4439	44'0"	102"	8'2 1/4"	8'8"	35'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	6926	22,500	18,000	15,574
	MTG 4839	48'0"	102"	8'2 1/4"	8'8"	39'10"	7'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	7406	22,500	18,000	15,094

## MotorTrac® A-frame Gooseneck

	MODEL	Overall:				Interior:				Axle #	Rear Door Width	Rear Door Height	Platform Height	Wheel Box Clearance	Curb Weight	GVWR	GAWR	Average Payload Capacity	
		L	W (Axle)	W (Body)	H	L (Lower Deck)	L (Upper Deck)	W	H (Lower Deck)										H*** (Upper Deck)
5 Ton	MTGA 2425	24'0"	102"	8'2 1/4"	8'8"	15'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	4120	14,700	12,000	10,580
	MTGA 2825	28'0"	102"	8'2 1/4"	8'8"	19'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	4610	14,700	12,000	10,090
	MTGA 3225	32'0"	102"	8'2 1/4"	8'8"	23'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	5100	14,700	12,000	9,600
	MTGA 3625	36'0"	102"	8'2 1/4"	8'8"	27'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	5580	14,700	12,000	9,120
	MTGA 4025	40'0"	102"	8'2 1/4"	8'8"	31'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	6060	14,700	12,000	8,640
	MTGA 4425	44'0"	102"	8'2 1/4"	8'8"	35'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	6540	14,700	12,000	8,160
9 Ton	MTGA 4825	48'0"	102"	8'2 1/4"	8'8"	39'10"	3'11"	7'11"	6'6"	2'10"	2	90 3/4"	80"	20"	80"	7020	14,700	12,000	7,680
	MTGA 2439	24'0"	102"	8'2 1/4"	8'8"	15'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	4506	22,500	18,000	17,994
	MTGA 2839	28'0"	102"	8'2 1/4"	8'8"	19'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	4996	22,500	18,000	17,504
	MTGA 3239	32'0"	102"	8'2 1/4"	8'8"	23'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	5486	22,500	18,000	17,014
	MTGA 3639	36'0"	102"	8'2 1/4"	8'8"	27'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	5966	22,500	18,000	16,534
	MTGA 4039	40'0"	102"	8'2 1/4"	8'8"	31'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	6446	22,500	18,000	16,054
9 Ton	MTGA 4439	44'0"	102"	8'2 1/4"	8'8"	35'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	6926	22,500	18,000	15,574
	MTGA 4839	48'0"	102"	8'2 1/4"	8'8"	39'10"	3'11"	7'11"	6'6"	2'10"	3	90 3/4"	80"	20"	80"	7406	22,500	18,000	15,094

\*\*\* May Vary With Tow Vehicle Hitch Requirements

All Specifications and Features Subject To Change Without Notice.



First Class Interior Accommodations



Extruded Aluminum Ramp Toe Extension



5000 lb. D-Ring Tie-Downs (4)



Exclusive AlumaSport™ Aluminum Wheels

## TURN 2 Deluxe Interior Package

The stylish **Turn 2 Deluxe Interior Package** from Wells Cargo is for racers who prefer to push the envelope rather than hang with the pack. Shown here on our newly re-engineered MotorTrac 2000 Racing Series, this generous assortment of premium options is sure to leave a lasting impression. From the sturdy workbench to our exclusive AlumaSport™ Aluminum wheels, only Wells Cargo could build a racing trailer with so much to offer. Beyond just show-stopping good looks, you get the piece-of-mind knowing that there's 49 years of customizing experience behind every trailer. With the **Turn 2 Deluxe Interior Package**, the best part of heading off to the track just might be the trip there.

### Turn 2 Deluxe Interior Package Includes:

- Tag-a-longs Lengths: 18' to 32'. Gooseneck Lengths: 20' to 48'.
- Anodized Aluminum Front and Rear Corner Caps
- Anodized Rear Door Header and Rear Crossmember
- Sub-Floor Spare Tire Carrier
- AlumaSport™ 15" Aluminum Wheels\*
- 7'0" Inside Height
- Extruded Aluminum Ramp Extension
- 5000 lb. D-Ring Tie-Downs (4)
- Aluminum Tread Plate Floor & Ramp Door Deck
- White Aluminum Sidewall Liner and Ceiling
- Insulated Sidewalls and Ceiling
- Workbench with Overhead Cabinet
- 12 Volt Dome Light (1 add'l)
- Fluorescent Light Fixtures (4)
- 500 Watt Recessed Exterior Flood Lights (2)
- 3-Way 12-Volt Wall Switches (2)
- 30 AMP, 120 Volt 4 Circuit Service Panel with Breaker
- Cable Hatch and 25' Shoreline
- Duplex Wall Receptacles (3)

\* The AlumaSport wheel will be substituted with an aluminum Vented Mod wheel on certain larger Gooseneck models with 16" tires.

Authorized Wells Cargo Dealer:



©Wells Cargo, Inc. 2003  
Form: MT2000-203R1103



# 4000 RACING SERIES



# 4000 RACING SERIES



## Model MT2624W-4000

(featuring optional Extruded Aluminum Ramp Toe Extension)

### SPECIFICATIONS

MODEL	MT2024W-4000	MT2424W-4000	MT2624W-4000	MT2824W-4000
BODY: LENGTH	20'0"	24'0"	26'0"	28'0"
WIDTH	98 1/4"	98 1/4"	98 1/4"	98 1/4"
OVERALL: LENGTH	24'0"	28'0"	30'0"	32'0"
WIDTH	102"	102"	102"	102"
HEIGHT	8'5"	8'5"	8'5"	8'7"
INTERIOR: LENGTH	19'9"	23'9"	25'9"	27'9"
WIDTH	7'11"	7'11"	7'11"	7'11"
HEIGHT	6'6"	6'6"	6'6"	6'6"
WHEEL BOX CLEARANCE	81"	81"	81"	81"
PLATFORM HEIGHT	17"	17"	17"	18"
TIRE SIZE/LOAD RANGE	15" /D	15" /D	15" /D	15" /D
WHEEL BOLT PATTERN	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5	6-Bolt/5.5
HITCH TO TOP OF BALL	19"	19"	19"	21"
HITCH WEIGHT (% of Curb Weight)	10-15%	10-15%	10-15%	10-15%
CURB WEIGHT (lb.)	3300	3700	4200	4700
GVWR (lb.)	11,000	11,000	11,000	11,000
GAWR (lb.)	10,000	10,000	10,000	10,000
AVG. PAYLOAD CAPACITY (lb.)	7700	7300	6800	6300
REAR RAMP DOOR: WIDTH	90 1/2"	90 1/2"	90 1/2"	90 1/2"
HEIGHT	79"	79"	79"	79"
WARRANTY	6-Years	6-Years	6-years	6-Years

### FEATURES

- Recessed Rear Ramp Door with Dual Spring Assist
- Rear Cornerpost Stabilizer Jacks
- Reinforced 4" Recessed Beavertail
- 36" Side Door with Rotary Style Flush Lock
- Recessed Step at Side Door
- 3/4" Exterior Grade Plywood Floor (undercoated)
- 1/4" White Vinyl Interior Sidewall Liner
- 1/4" White Vinyl Ceiling Liner
- 12-Volt Dome Lights (2) with Wall Switch
- LED Clear Wraparound Stop/Tail/Turn Lights
- LED Clearance Lights



Standard Interior Floor and Sidewall Liner

- LED Safety Package (High Profile Brake Lights & Side Turn Indicators)
- 24" ATP Stone Guard with Intergrated Corners
- Cast Aluminum Front & Rear Top Corners
- Polished Stainless Steel Front Cap
- Bright Anodized Aluminum Front & Rear Corner Covers
- Satin Anodized Aluminum Fenderettes
- .040 Prefinished Aluminum Exterior Skin (3 colors - white, red & black)
- Bonded Exterior Skin Application for Smooth Appearance
- Aluminum Seamless Roof
- Tubular Steel Main Rails
- Full Height C-Channel Crossmembers & Outriggers
- Chassis Fully Undercoated with CPC (Corrosion Preventative Compound)
- 3-Piece A-Frame with 2 5/16" Ball Coupler Hitch
- Top Crank Jack Ram Hoist with Sand Pad
- D.O.T. Compliant Safety Chains with Clevis Slip Hook & Latch
- Torflex® Rubber Torsion Tandem Axles (10" Up Trailing)
- E-Z Lube Hubs
- 15" Radial Tires on AlumaSport Aluminum Wheels
- Electric Brakes with Weather Resistant Wiring
- Wet Cell Battery Breakaway System
- 7-way Pigtail Connector

Authorized Wells Cargo Dealer:



©Wells Cargo, Inc. 2003  
Form: MT4000-203R403